

» GPS6000-LITE

HIGH ACCURACY TIMING FOR YOUR TIME SERVER



KEY BENEFITS

High accuracy timing for your time server

Reliable performance, even in weak signal and hostile RF environments

30 nsec timing accuracy

Simple installation into your data centre using existing cat 5 structured cabling

An economical GPS timing solution

The GPS6000-LITE Time Receiver accurately synchronises your time server with international atomic standards.

ACCURATE TIMING

The GPS6000-LITE provides highly accurate time data. With 32 satellite parallel tracking and class-leading high performance design, the GNSS decoder supplies time data accurate to within 30 nsec of UTC. The user programmable cable delay compensation ensures timing accuracy is maintained, even over long cable runs.

RELIABLE PERFORMANCE

The system has been engineered to ensure reliable performance. The high sensitivity GPS6000 decoder allows for operation in the most demanding weak signal and hostile RF environments. The GPS6000 fully integrates with your time server, providing real time diagnostics and active antenna monitoring.

SIMPLE INSTALLATION

Installing the GPS6000 is simple. Both cables are supplied pre-terminated. The GPS6000 has also been purpose designed to allow cost saving installation into your data centre, optionally connecting to your time server via existing cat 5 structured cabling.

Timing performance:

Synchronised accuracy: 30 nsec (1 sigma)

GNSS decoder:

GNSS engine: Anti-jam capable, 32 satellite parallel tracking

Minimum acquisition sensitivity: -148dBm (cold start)

Minimum tracking sensitivity: -160dBm

Operating temperature: 0 to 50°C

Relative humidity: 0% - 95%, noncondensing

Enclosure: 85 x 65 x 30mm (3.35" x 2.56" x 1.18") aluminium enclosure with wall mount brackets

Weight: 0.2 kg

Cable delay compensation: User programmable

Status monitoring: Fully integrated diagnostic system with active antenna monitoring. Multi-colour status LED

Antenna:

Antenna: IP67 adhesive mount GPS antenna

Gain: 29dB

Noise: 1.3dB

Operating temperature: -30°C to +75°C

Dimensions: 33 x 44 x 14mm (1.30" x 1.73" x 0.55")

Cabling:

Antenna cable: 3m (9ft) captive pre-terminated RG-174 SMA coaxial

Output cable: 5m (16ft) pre-terminated Belden 9502 (two pair plus drain 24 AWG stranded cable with 100% foil shield and semi-rigid, sunlight resistant, Polyvinyl Chloride (PVC) jacket)

Warranty & Support:

Warranty: 5 years

Support: Free-of-charge lifetime technical support

Standards compliance:

Electrical Safety: BS EN 60950-1:2006

Radio Disturbance: BS EN 55022:2006

Immunity Characteristics: BS EN 55024:2003

RoHS: RoHS-Compliant

Scope of supply:

GPS6000-LITE scope of supply: 1 x GNSS decoder
1 x GPS antenna with 3m cable
1 x 5m output cable

Options:

GPS6000-OUT-15: 15m (49ft) output cable

GPS6000-OUT-50: 50m (164ft) output cable

GPS6000-OUT-150: 150m (492ft) output cable

(Non-standard cable lengths are available upon request)